


Specifications

Printhead	8 on-demand piezo heads in a staggered array
Print Resolutions	1800 dpi
Print Speed (4 Color Mode)	86.1 ft ² /hr (8 m ² /hr)
Maximum Print Area	27.9" x 20.0" (710 x 510 mm)
Maximum media area	30" x 24"
Maximum Media Thickness	up to 6.02" (153 mm)
Maximum Media Weight	66.0 lbs. (30.0 kg)
Ink Type	Rigid: LH-100, Flexible: LUS-120, LUS-150
Interface	Ethernet 1000BASE-T, USB2.0 Hi-speed
Power Supply	Single phase AC100-240V +6%/-10% 50/60Hz ± 1
Power Consumption	AC100V: 1.3kW or less
Operational Environment	Temperature 59° – 86° F (15-30° C) Humidity: 35–65 % RH (Non condensing)
Dimensions (W x D x H)	87" x 62" x 51" (220.3 x 158 x 129.3 cm)
Weight	728 lbs. (330 kg)
Certifications	VCCI class A, FCC class A, ETL UL 62368-1 CE Mark and RoHS), CB, REACH, GREENGUARD Gold

Inks

UV curable ink (LH-100)	Cyan	Magenta	Yellow	
250ml Bottle	I-LH100-C-B2-1	I-LH100-M-B2-1	I-LH100-Y-B2-1	I-LH100-B-B2-1
1L Bottle	LH100-C-BA	LH100-M-BA	LH100-Y-BA	LH100-B-BA
UV curable ink (LUS-120)	Cyan	Magenta	Yellow	
250ml Bottle	I-LUS12-C-B2-1	I-LH100-M-B2-1	I-LUS12-Y-B2-1	I-LUS12-B-B2-1
1L Bottle	LUS12-C-BA	LUS12-M-BA	LUS12-Y-BA	LUS12-B-BA
UV curable ink (LUS-350)	Cyan	Magenta	Yellow	B
1L Bottle	LUS35-C-BA	LUS35-M-BA	LUS35-Y-BA	LUS35-B-BA
UV Primer (PR-200)				
250ml Bottle				PR-200

1L Bottle



PR