

Specifications

Printhead [ⓧ]	Twelve on-demand piezo heads in a staggered array
Print resolution	X: 360 dpi, 540 dpi, 720 dpi, 1080 dpi Y: 360 dpi, 540 dpi, 720 dpi
Print speed (4 color mode)	up to 1937.504 SqFt/Hr (180 m2/)
Maximum Print Area	129.5" (3290 mm)
Maximum media width	129.9" (3300 mm)
Maximum Media Thickness	up to 0.04" (1 mm)
Maximum Media Weight	286.9 lbs. (130.0 kg)
Ink Type	U.S. & Canada- Sb310 Mexico, Central & South America- Sb310
Interface	Ethernet 1000BASE-T, USB2.0 Hi-speed
Power Supply [ⓧ]	Single-phase AC200 – 240V ±10%, 50/60Hz ±1Hz
Power Consumption	AC200V: 6,900W or less
Operational Environment	Temperature 68° – 86° F (20-30° C) Humidity: 35–65 % RH (Non condensing)
Dimensions (W × D × H)	221.3" x 70.9" x 71.7" (562.1 x 180.1 x 182.1 cm)
Weight	Main unit: 3,306.9 lbs. (1,500 kg) Ink supply unit: 66.1 lbs. (30 kg)

Certifications	VCCI class A, FCC class A, ETL UL 60950-1, CE M and RoHS), CB, REACH
----------------	--

Inks

Dye-Sublimation ink (Sb310)	Blue	Magenta	Yellow
2L Bottles	SB310-BLT-BB	SB310-MT-BB	SB310-YT-BB