

# Specifications

Printhead	Twelve on-demand piezo heads in a staggered array
Print resolution	X: 360dpi, 540dpi, 720 dpi, 1,080dpi / Y: 540dpi, 720dpi
Print speed (4 color mode)	up to 1399.308 SqFt/Hr (130 m <sup>2</sup> /h)
Maximum Print Area	129.5" (3290 mm)
Maximum media width	129.9" (3300 mm)
Maximum Media Thickness	up to 0.04" (1 mm)
Maximum Media Weight	286.9 lbs. (130.0 kg)
Ink Type	U.S. & Canada- Sb320   Mexico, Central & South America- Sb320
Interface	Ethernet 1000BASE-T, USB2.0 Hi-speed
Power Supply	Main unit: Single-phase AC200 – 240V±10%, 50/60 Hz Fixation heater: Three-phase: AC200V±10%, 50/60 Hz
Power Consumption	AC200V: Main unit – 7 kVA or less   Fixation heater: 10 kVA or less
Operational Environment	Temperature 68° – 86° F (20-30° C) Humidity: 35–65 % RH (Non condensing)
Dimensions (W × D × H)	221.3" x 120.1" x 71.7" (562.1 x 305.1 x 182.1 cm)
Weight	Main unit: 5,269 lbs. (2,390 kg) Ink supply unit: 66.1 lbs. (30 kg) Inverter: 308.6 lbs. (140 kg)

Certifications	<p>VCCI class A / FCC class / UL 775 compliance / CE / REACH</p> <p>Vertical non-contact heating system</p> <p>Standard: 356° F (180° C)</p> <p>Maximum temperature: 392° F (200° C)</p> <p>Temperature fluctuation: ±5 degC (±41 degF)</p>
----------------	---

# Inks

Dye Sublimation Ink (SB320)	Blue	Magenta	Yellow
2L Ink Bottles	SB320-BLD-BB	SB320-MD-BB	SB320-YD-BB