

Specifications

Printhead	UJF-3042MkII e: Three on-demand piezo heads in a UJF-3042MkII EX e: Four on-demand piezo heads in a
Print Resolutions	Maximum: 1200 x 1200 dpi
Print Speed (4 color mode)	26.7 ft ² /hr (2.5m ² /hr)
Maximum Print Area	11.8" x 16.5" (300 x 420 mm)
Maximum media area	26" x 18"
Maximum Media Thickness	up to 6.02" (153 mm)
Maximum Media Weight	11.0 lbs. (5.0 kg)
Ink Type	Rigid: LH-100, Flexible: LUS-120, LUS-150
Interface	Ethernet 1000BASE-T, USB2.0 Hi-speed
Power Supply	Single-phase AC100-240V, ±10%, 50/60Hz ±1Hz
Power Consumption	AC100V: 1,000W or less
Operational Environment	Temperature 68° – 86° F (20-30° C) Humidity: 35–65 % RH (Non condensing)
Dimensions (W × D × H)	53.4" x 50.8" x 33.7" (135.6 x 129 x 85.6 cm)
Weight	297.6 lbs. (135 kg)
Certifications	VCCI class A / FCC class A / ETL UL 60950-1 / CB directive, and RoHS)/ REACH / Energy Star / IEC60

Inks

UV Curable Ink (LH-100)	Cyan	Magenta	Yellow
250ml Bottle	I-LH100-C-B2-1	I-LH100-M-B2-1	I-LH100-Y-B2-1
1L Bottle	LH100-C-BA	LH100-M-BA	LH100-Y-BA
Curable Ink (LUS-120)	Cyan	Magenta	Yellow
250ml Bottle	I-LUS12-C-B2-1	I-LUS12-M-B2-1	I-LUS12-Y-B2-1
1L Bottle	LUS12-C-BA	LUS12-M-BA	LUS12-Y-BA
UV Curable Ink (LUS-150)	Cyan	Magenta	Yellow
1L Bottle	LUS15-C-BA	LUS15-M-BA	LUS15-Y-BA
UV Primer (PR-200)	Primer		
250ml Bottle	PR200		

1L Bottle

PR200