TECHNICAL DATA SHEET

Monarch "Improved" HN/RLD Imagesetting Film

Application Dot Works Monarch "Improved" is a designed for use in recorders with

helium neon lasers and red laser diodes.

• Excellent sharpness

Wide exposure and development latitude

High practical density

· Linear output for conventional screening

· Approved for stochastic screening

· Anti-static protection

Spectral Sensitivity 633 - 670 NM

Exposure Guideline

Adjust image intensity to achieve a density of 4.8. Then run standard

calibration software to achieve desired dot values in each step.

Processing:

Developer Majestic 650 Developer 3:1, 95°F or 35°C for 20 - 40 sec.

Fixer URFC Fixer 2:1

Hardener URHS Hardener 72 oz. to 20 gal.

Replenishment Majestic 650 Developer at .4 cc/sq. in.

URFC Fixer at .5 cc/sq. in.

Safelight Handling EncapSulite T20/ND.75 dark green safelight, no closer than 4 feet.

Storage Store in a cool, dry area below 70°F or 21°C and at 55% relative

humidity.

Recognition Systems, Inc.

30 Harbor Park Drive Port Washington, NY 11050 T: 516-625-5000 / F: 516-625-1507 www.dotworks.com



Brook Street Works
Brook Street, Hazel Grove
Stockport, SK7 4QX UK
T: 0161-456-6529 / F: 0160-456-9893