

# TECHNICAL DATA SHEET

## Ultra Clear Decal Window Film

### DESCRIPTION:

- Premium quality printable clear PVC film offers “optical” clarity
- Super smooth polyester liner gives “crystal” quality before/after application
- Solvent acrylic adhesive ensures long terms application
- Ideal for windows décor or window graphic

PARAMETER		VALUE
Film	TYPE	100um Optical clear PVC films
	Opacity	3%
	Finish	GLOSS (95@60°)
	E value (% at break)	220%/230% (MD/CD)
	Shrinkage	3%/0.5% (MD/CD)
Glue	Materials	25um solvent based acrylic glue
	Type	Clear soft removable
	Init tack (20min peel)/(N/in)	4N
	Hold: 9.8N/in <sup>2</sup> (Hours)	72Hours
	180 Peel (N/in)	5N
Liner	Thickness	125um
	Type	clear matte PET
Shelf time		24 Months
Applying temperature		-5°C- 50°C
Outdoor durability		24Months

### PRINTING INK

Solvent	Eco-Sol	Aqueous Dye	Aqueous Pigment	UV	Latex
	Y			Y	Y

### APPLICATION

Billboard Graphic	Rigid Board Graphic	Window Graphic	Wall Graphic	Floor Graphic	Vehicle Graphic	Signs
		Y				Y

NOTE: All values shown are for reference only. The mentioned data are average of test results and should not be used for the purpose of lawsuit or warranty.

